



Product Service

# Attestation of Conformity

No. N8A 116659 0002 Rev. 00

**Holder of Attestation:** **Yancheng Runda PV Co., Ltd.**

No.199 Yanqiao Road  
Tanghe Street, Jianhu County  
224799 Yancheng, Jiangsu Province  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**  
**Mono-Crystalline Silicon Photovoltaic Module**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704062313003-00

**Date,** 2023-03-03

( Zhulin Zhang )

Page 1 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.





Product Service

# Attestation of Conformity

No. N8A 116659 0002 Rev. 00

## Model(s):

RSxxxM6-72 (xxx=340-400 in step of 5W)  
 RSxxxM6-60 (xxx=285-330 in step of 5W)  
 RSxxxM6-54 (xxx=255-300 in step of 5W)  
 RSxxxM6-48 (xxx=230-265 in step of 5W)  
 RSxxxM6-36 (xxx=170-200 in step of 5W)  
 RSxxxS-144 (xxx=380-425 in step of 5W)  
 RSxxxS-120 (xxx=320-355 in step of 5W)  
 RSxxxS7-144 (xxx=425-465 in step of 5W)  
 RSxxxS7-120 (xxx=355-385 in step of 5W)  
 RSxxxS7-132 (xxx=390-425 in step of 5W)  
 RSxxxS8-144 (xxx=525-550 in step of 5W)  
 RSxxxS8-132 (xxx=485-500 in step of 5W)  
 RSxxxS8-120 (xxx=440-455 in step of 5W)  
 RSxxxS8-108 (xxx=390-410 in step of 5W)  
 RSxxxS8-84 (xxx=300-320 in step of 5W)  
 RSxxxS8-60 (xxx=220-230 in step of 5W)  
 RSxxxS8-56 (xxx=200-210 in step of 5W)  
 RSxxxS8-54 (xxx=195-205 in step of 5W)  
 RSxxxS8-44 (xxx=160-165 in step of 5W)  
 RSxxxS9-132 (xxx=635-665 in step of 5W)  
 RSxxxS9-120 (xxx=570-605 in step of 5W)  
 RSxxxS9-108 (xxx=520-545 in step of 5W)  
 RSxxxS9-96 (xxx=465-480 in step of 5W)  
 RSxxxS9-110 (xxx=530-550 in step of 5W)  
 RSxxxS9-100 (xxx=485-500 in step of 5W)  
 RSxxxS9-90 (xxx=435-450 in step of 5W)  
 RSxxxS9-80 (xxx=385-400 in step of 5W)  
 RSxxxS9-132NT (xxx=675-695 in step of 5W)  
 RSxxxS9-120NT (xxx=615-630 in step of 5W)  
 RSxxxS9-108NT (xxx=555-565 in step of 5W)  
 RSxxxS9-96NT (xxx=490-505 in step of 5W)  
 RSxxxS8-144NT (xxx=550-575 in step of 5W)  
 RSxxxS8-132NT (xxx=505-525 in step of 5W)  
 RSxxxS8-120NT (xxx=460-480 in step of 5W)  
 RSxxxS8-108NT (xxx=415-430 in step of 5W)

### Black series:

RSxxxM6B-72 (xxx=340-400 in step of 5W)  
 RSxxxM6B-60 (xxx=285-330 in step of 5W)  
 RSxxxM6B-54 (xxx=255-300 in step of 5W)  
 RSxxxM6B-48 (xxx=230-265 in step of 5W)  
 RSxxxM6B-36 (xxx=170-200 in step of 5W)  
 RSxxxSB-144 (xxx=380-425 in step of 5W)  
 RSxxxSB-120 (xxx=320-355 in step of 5W)  
 RSxxxS7B-144 (xxx=425-465 in step of 5W)  
 RSxxxS7B-120 (xxx=355-385 in step of 5W)  
 RSxxxS7B-132 (xxx=390-425 in step of 5W)  
 RSxxxS8B-144 (xxx=525-550 in step of 5W)  
 RSxxxS8B-132 (xxx=485-500 in step of 5W)  
 RSxxxS8B-120 (xxx=440-455 in step of 5W)  
 RSxxxS8B-108 (xxx=390-410 in step of 5W)  
 RSxxxS8B-84 (xxx=300-320 in step of 5W)  
 RSxxxS8B-60 (xxx=220-230 in step of 5W)  
 RSxxxS8B-56 (xxx=200-210 in step of 5W)  
 RSxxxS8B-54 (xxx=195-205 in step of 5W)  
 RSxxxS8B-44 (xxx=160-165 in step of 5W)  
 RSxxxS9B-132 (xxx=635-665 in step of 5W)  
 RSxxxS9B-120 (xxx=570-605 in step of 5W)  
 RSxxxS9B-108 (xxx=520-545 in step of 5W)  
 RSxxxS9B-96 (xxx=465-480 in step of 5W)  
 RSxxxS9B-110 (xxx=530-550 in step of 5W)  
 RSxxxS9B-100 (xxx=485-500 in step of 5W)

Page 2 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



TUV®



# Attestation of Conformity

No. N8A 116659 0002 Rev. 00

RSxxxS9B-90 (xxx=435-450 in step of 5W)  
 RSxxxS9B-80 (xxx=385-400 in step of 5W)  
 RSxxxS9B-132NT (xxx=675-695 in step of 5W)  
 RSxxxS9B-120NT (xxx=615-630 in step of 5W)  
 RSxxxS9B-108NT (xxx=555-565 in step of 5W)  
 RSxxxS9B-96NT (xxx=490-505 in step of 5W)  
 RSxxxS8B-144NT (xxx=550-575 in step of 5W)  
 RSxxxS8B-132NT (xxx=505-525 in step of 5W)  
 RSxxxS8B-120NT (xxx=460-480 in step of 5W)  
 RSxxxS8B-108NT (xxx=415-430 in step of 5W)

**Transparent series:**

RSxxxS8T-144 (xxx=525-550 in step of 5W)  
 RSxxxS8T-132 (xxx=485-500 in step of 5W)  
 RSxxxS8T-120 (xxx=440-455 in step of 5W)  
 RSxxxS8T-108 (xxx=390-410 in step of 5W)  
 RSxxxS8T-84 (xxx=300-320 in step of 5W)  
 RSxxxS8T-60 (xxx=220-230 in step of 5W)  
 RSxxxS8T-56 (xxx=200-210 in step of 5W)  
 RSxxxS8T-54 (xxx=195-205 in step of 5W)  
 RSxxxS8T-44 (xxx=160-165 in step of 5W)  
 RSxxxS9T-132 (xxx=635-665 in step of 5W)  
 RSxxxS9T-120 (xxx=570-605 in step of 5W)  
 RSxxxS9T-108 (xxx=520-545 in step of 5W)  
 RSxxxS9T-96 (xxx=465-480 in step of 5W)  
 RSxxxS9T-110 (xxx=530-550 in step of 5W)  
 RSxxxS9T-100 (xxx=485-500 in step of 5W)  
 RSxxxS9T-90 (xxx=435-450 in step of 5W)  
 RSxxxS9T-80 (xxx=385-400 in step of 5W)  
 RSxxxS9T-132NT (xxx=675-695 in step of 5W)  
 RSxxxS9T-120NT (xxx=615-630 in step of 5W)  
 RSxxxS9T-108NT (xxx=555-565 in step of 5W)  
 RSxxxS9T-96NT (xxx=490-505 in step of 5W)  
 RSxxxS8T-144NT (xxx=550-575 in step of 5W)  
 RSxxxS8T-132NT (xxx=505-525 in step of 5W)  
 RSxxxS8T-120NT (xxx=460-480 in step of 5W)  
 RSxxxS8T-108NT (xxx=415-430 in step of 5W)  
 xxx is standing for rated output power at STC

**Parameters:**

Safety Class:	Class II
Max. System Voltage:	1500V DC
Construction:	Framed, with Junction box, cable and connector.
Fire Safety Class:	Class C according to UL790

**Tested according to:**

EN IEC 61730-1:2018  
 EN IEC 61730-1:2018/AC:2018-06  
 EN IEC 61730-2:2018  
 EN IEC 61730-2:2018/AC:2018-06

Page 3 of 3

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

