

Tarzan Series

500W MBB Monocrystalline Module Half-cell Module S9-100 485~500W



- ▲ Higher output power
- ▲ Module efficiency up to 21.0%
- ▲ Lower temperature coefficient



- ▲ Lower LCOE (Levelized Cost Of Energy)
- ▲ High Power output lead to lower BOS cost




- ▲ ISO9001:2015 Quality Management system
- ▲ ISO14001:2015 Environmental Management System
- ▲ ISO45001:2018 Occupational Health and Safety Management System



- ▲ Salt Mist Corrosion Protect
- ▲ Ammonia Resistance




Excellent Potential Induced Degradation Resistance



Excellent Wind Load 2400Pa & Snow Load 5400Pa Under Certain Installation Method

Runda's linear performance warranty



12 Years
Material & Craft
Quality
assurance

25 Years
85% output
Power
guarantee



Tarzan Series

RS485~500S9-100

Electrical Characteristics(STC*)

Power Output(Wp)	485	490	495	500
Max Power Tolerance(W)	0-5	0-5	0-5	0-5
Module Efficiency(%)	20.4	20.6	20.8	21.0
Voltage Mpp-Vmpp(V)	28.23	28.44	28.63	28.84
Current Mpp-Impp(A)	17.18	17.23	17.29	17.34
Voltage Open Circuit-Voc(V)	34.03	34.27	34.49	34.73
Short Circuit Current-Isc(A)	18.25	18.30	18.36	18.41

*STC:Irradiance 1000 W/m²,Cell Temperature 25°C,Air Mass AM1.5

Electrical Characteristics(NMOT*)


Power Output(Wp)	372.59	376.43	380.28	384.12
Voltage Mpp-Vmpp(V)	25.73	25.92	26.10	26.28
Current Mpp-Impp(A)	14.48	14.52	14.57	14.61
Voltage Open Circuit-Voc(V)	31.42	31.64	31.84	32.07
Short Circuit Current-Isc(A)	15.52	15.56	15.61	15.65

*NMOT:Irradiance 800 W/m²,Ambient Temperature 20°C,Air Mass AM1.5, Wind Speed 1m/s




Mechanical Data

Dimension Of Module	2172*1096*35mm
Weight	26kg
Glass	High transmission glass 3.2mm
Cables	4mm ² /300mm or Customized Length
Junction Box	IP68,3 bypass diodes
Connector	MC4 compatible

Module Structure Drawing



Curves(500W)



Packaging Configuration

Container	40'HQ
Pieces Per Pallet	31
Pallets Per Container	20
Pieces Per Container	620

Working Conditions

Max System Voltage(VDC)	1500V
Max Series Fuse Rating	30A
Maximum Load Capacity	Snow 5400Pa/Wind 2400Pa
Operating Temperature	-40°C~+85°C
Safety Class	II

Temperature Ratings

Temperature Coefficients of Isc(%/°C)	0.046
Temperature Coefficients of Voc(%/°C)	-0.266
Temperature Coefficients of Pmpp(%/°C)	-0.354
NMOT	45±2°C