

## S8R-132GANT

**N-type  
Bifacial Dual Glass  
Mono Module**

**605 - 630W** / Power Output

**0~5W** / Pmax Tolerance

**23.32%** / Maximum Module Efficiency



### Outstanding Low Light Performance

Higher power output even under low-light environments like on cloudy or foggy days.



### Better Temperature Coefficient

Higher power generation under working conditions, thanks to passivating contact cell technology



### Lower LCOE

Higher bifaciality, higher power output and lower BOS cost



### Wider Applicability

More application scenes like BIPV, vertical installation, snowfield, high-humid, windy and dusty area



### 10%-30% Additional Power Generation

30 years lifespan brings 10%-30% additional power generation comparing with conventional P-type module



### Zero LID (Light Induced Degradation)

N-type solar cell has no LID naturally which can increase power generation



### PID Resistance


Excellent Anti-PID performance guarantee via optimized mass-production process and materials control



### Enhanced Mechanical Load

Certified to withstand: wind load (2400 Pascal) and snow load (5400 Pascal)

### Linear Performance Warranty



**15** years

Product quality & process guarantee

**30** years

Linear power guarantee

**0.40** %

Annual degradation

### Product Certification

ISO9001: 2015: Quality Management System

ISO14001: 2015: Environment Management System

ISO45001: 2018: Occupational health and safety management systems

IEC61215, IEC61730, IEC62716




\* Different markets have different certification requirements.

Also, the products are under rapid innovation.

Please confirm the certification status with regional sales representatives.

### Module Specification

Cell Type	132 [ 2 x ( 11 x 6 ) ] / 182*105mm
Dimensions (mm)	2382*1134*30
Weight (kg)	34.5
Front Cover	2.0mm, Anti-Reflection Coating
Rear Cover	2.0mm, Heat Strengthened Glass
Junction Box	IP68 (3 diodes)
Cables	TUV 1x4.0mm <sup>2</sup> , (+):300mm/(-):300mm or Customized length
Connector Type	MC4-EVO2 / MC4 compatible



### Electrical Specifications

Module Type	RS605S8R-132GANT		RS610S8R-132GANT		RS615S8R-132GANT		RS620S8R-132GANT		RS625S8R-132GANT		RS630S8R-132GANT	
Testing Condition	STC <sup>1</sup>	NOCT <sup>2</sup>	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax/W)	605	462	610	466	615	470	620	474	625	478	630	482
Maximum Power Current (Imp/A)	15.28	12.10	15.34	12.12	15.39	12.15	15.46	12.17	15.52	12.20	15.58	12.22
Maximum Power Voltage (Vmp/V)	39.60	38.19	39.77	38.44	39.97	38.71	40.12	38.96	40.28	39.20	40.44	39.44
Short-circuit Current (Isc/A)	16.00	12.72	16.05	12.74	16.10	12.77	16.15	12.79	16.20	12.82	16.25	12.84
Open-circuit Voltage (Voc/V)	47.90	46.00	48.10	46.30	48.30	46.60	48.50	46.90	48.70	47.20	48.90	47.50
Module Efficiency (%)	22.40		22.58		22.77		22.95		23.14		23.32	

<sup>1</sup> STC: Irradiance 1000W/m<sup>2</sup>, Cell Temperature 25°C, AM 1.5

<sup>2</sup> NOCT: Irradiance 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1m/s

### Electrical Specifications(BNPI<sup>1</sup>)

Nameplate Power (W)	605	610	615	620	625	630
Maximum Power (Pmax/W)	659	665	670	676	681	687
Maximum Power Current (Imp/A)	16.66	16.72	16.78	16.85	16.91	16.98
Maximum Power Voltage (Vmp/V)	39.60	39.77	39.97	40.12	40.28	40.44
Short-circuit Current (Isc/A)	17.44	17.49	17.55	17.60	17.66	17.71
Open-circuit Voltage (Voc/V)	47.90	48.10	48.30	48.50	48.70	48.90

<sup>1</sup> BNPI: Front radiation 1000W/m<sup>2</sup>, Rear radiation 135W/m<sup>2</sup>, Module temperature 25°C, AM=1.5

### Temperature Characteristics


Nominal Operating Cell Temperature (NOCT/°C)	42±2
Temperature Coefficient of Pmax (%/°C)	-0.310
Temperature Coefficient of Voc (%/°C)	-0.26
Temperature Coefficient of Isc (%/°C)	+0.046

### Packaging

Container	40HQ (Inner diameter length 12300mm)
Pallet Dimensions (mm)	2420*1130*2540
Pieces per Pallet	36
Pieces per Container	720

### Operating Conditions

Operating Temperature (°C)	-40 to +85
Maximum System Voltage (V)	1500 DC (IEC)
Overcurrent Protection Rating (A)	30
Protection Class	Class II
Max. Test Load, Push/Pull (Pa)	Front 5400 / Back 2400



Yancheng Runda PV CO.,Ltd

Add: No.199 Yanqiao Road, Tanghe Street, Jianhu County, Yancheng City Jiangsu Province, China

Tel: +86-0510-83801000

E-mail: sales@rundapv.com

Website: www.rundapv.com

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.

© 2024 Runda Solar All rights reserved. Contents included in this datasheet are subject to change without notice.

No special undertaking or warranty for the suitability of special purpose or being installed in extraordinary surroundings is granted unless as otherwise specifically committed by manufacturer in contract document.

Version No.: Global\_EN\_2024\_11